

# 597 Temperature/Relative Humidity Pressure Sensor

---

**The 597 is an integrated Temperature, Relative Humidity and Pressure measurement sensor.** All sensing elements are of the highest quality and are specifically designed for continuous duty in hostile environments. The temperature sensor utilizes platinum RTD class 1/3B. Relative Humidity is based on our very accurate solid-state sensor design for continuous exposure to adverse climates. And the Barometric Pressure sensor is a piezo-resistive device designed for robustness, high accuracy and long-term stability.

All components are housed in a Multi-Plate naturally aspirated Radiation shield to reduce solar radiation heating errors. The shield consists of a series of white aluminum concentric plates, which allow air flow to pass through the shield, while blocking direct solar rays.

The 597 has both analog and digital outputs for maximum flexibility with additional connectivity options available with the optional 10600 Interface. Analog outputs provide conventional connections to data loggers and systems utilizing a voltage proportional to each of the three measurements.

Digital outputs are available as a serial data stream every second, or upon command by the data system. The digital outputs offer higher resolution and immunity to analog offset problems.

## Features

- Temperature, Humidity, Pressure
- Compact Design
- Powder Coated Anodized Aluminum Construction
- Digital and Analog Outputs
- Easy installation
- IP65 Weather Proof Rated



597 Temperature/Relative Humidity/Pressure Sensor

---

## Specifications

### Temperature

Range:	50°C to +70°C
Accuracy:	Digital: $\pm 0.1^\circ\text{C}$ Analog: $\pm 0.12^\circ\text{C}$ , 0-5 V output
Resolution:	Digital: $0.01^\circ\text{C}$ Analog: $0.01^\circ\text{C}$ , 0-5 V output

# 597 Temperature/Relative Humidity Pressure Sensor

## Specifications (continued)

### Relative Humidity

Range:	0 to 100%
Accuracy:	Digital: $\pm 0.8\%$ Analog: $\pm 1\%$ , 0-5 V output
Resolution:	Digital: 0.1% Analog: 0.1%

### Pressure

Range:	500 to 1100 hPa
Accuracy (1):	Digital: $\pm 0.30$ hPa Analog: $\pm 0.45$ hPa, 0-5 V output
Resolution:	Digital: 0.01 hPa Analog: 0.01 hPa, 0-5 V output

### Electrical

Measurement Rate Output:	1 Hz
Data Storage	None
Analog Signal	Output 0-5V (options 0-1V or 0-2.5V, select at time of purchase)
Digital Signal Output	RS-232C and SDI-12 and RS-485 (select at time of purchase)
Power supply	9-36VDC, 25mA @ 12VDC

### Mechanical

Temperature	-50°C to +70°C
Humidity	0 to 100%
Dimensions	Diameter: 7 in (178 mm) Length: 8 in (203 mm) Weight: 5 lb (2.3 kg)

(1) At 25°C

10600 Interface Option: Adds USB connectivity and convenience to Met One Instruments 597 Sensor and provides a power supply module for both module and sensor power.



REV MAR. 2018



**Met One**  
Instruments, Inc.

1600 Washington Blvd. • Grants Pass, Oregon 97526 • 541.471.7111 • [www.metone.com](http://www.metone.com)  
[sales@metone.com](mailto:sales@metone.com)