

## Model 6400 Visibility Sensor

**The Met One Instruments Model 6400 Visibility Sensor is designed to monitor visibility conditions over a range of 20ft-50miles (6m-80km).**

The Model 6400 includes both digital and relay outputs. Digital RS232 output at 300-38,400 Baud can be used to indicate the present visibility, provide diagnostic information, and provide access to the configuration and calibration options. The SPDT relay with configurable pull in and drop out set points can provide signals to a VMS or other optional user system.

Met One takes advantage of Belfort's proven experience with visibility technology in redesigning this new sensor for applications which require high accuracy over an extended range of visibility. These sensors are designed to provide both accuracy and reliability in a cost-effective package. The Model 6400 now features ease of field serviceability. Applications include synoptic stations, lighthouses, highways, resort areas, as well as shipboard and other marine platforms.

Visibility is detected using widely accepted principles of forward scattering. A high output infrared LED transmitter projects light into a sample volume and light scattered in a forward direction is collected by the receiver. The light source is modulated to provide excellent rejection of background noise and natural variations in background light intensity. The sensors can asynchronously stream RS232 visibility data at user configured intervals, or can be operated in the polled mode, outputting information only when asked. Visibility is also compared to the preset relay thresholds, so that when an alarm condition is reached, the relay output is switched. Visibility thresholds can be set to any value within the instrument range. These sensors are assembled around a compact, light-weight housing, which can be installed on a simple pipe mast. They are constructed entirely of corrosion resistant materials for durability. The standard unit includes small heaters to prevent condensation on the optics. Optional hood heaters are available for areas where the sensor will operate in freezing weather. Transmitter and receiver hoods are designed to divert precipitation away from the optical paths. A calibration kit is available for field calibration. Calibration is possible under most weather conditions. Belfort Visibility Sensors have earned a leading reputation with the world's foremost meteorological and transportation organizations. The Model 6400 Sensor continues this quality tradition at a more favorable cost.



### Features

- High Accuracy
- Proven Optical Technology
- Digital and Relay Outputs
- Selectable Relay Thresholds
- Compact, Lightweight Design
- Corrosion Resistance
- Meteorological Optical Range (MOR)

### Options

- **Calibration Kit (P/N 93001)**
- **Hood Heaters (Configurable)**
- **Analog Output (Configurable)**

Range:	20 ft. to 50 miles (6m to 80km)
Accuracy:	±10%
Scatter Angle:	42° nominal
Light Source:	Infrared LED
Outputs:	RS232/RS485 (300 - 38400 baud) SPDT Relay for Warning Signs, Signals, Alarms Analog Voltage: 0-1, 0-5, 0-10 vdc configurable Analog Current: 4-20 mA
Environmental:	-40° to 130° F (-40° to +55° C) 0 to 100% Humidity
Power Requirement:	+12 VDC 500 mA 6 watts
With Hood Heater:	30 watts
Dimensions:	38" w x 13" h x 16" d
Weight:	17.5 lbs. (7.9 kg)
Ingress Protection	IP66 (pending)

*Specifications are subject to change at any time.*